## ILOOK by Frigoglass Raising the bar on the FV range





www.frigoglass.com

## ILOOK, the benchmark cooler of the next generation

ILOOK is the evolution of the FV range, the most trusted cooler range in the global market. ILOOK combines all the best features of the FV line-up, such as robust construction, best-in-class performance and energy consumption as well as extended lifetime, with modern and premium aesthetics that differentiate your product at the POS and stimulate impulse purchase.



been incorporated into the grid to complete and enhance the brand's visual identity. The full metallic grid allows for increased durability.





Premium aesthetics



LED lighting Reduced noise

 $\left( \right)$ 



Best-in-class consumption



servicing

Foul-free





Premium aesthetics



LED lighting Reduced

noise



Best-in-class consumption



Easy servicing



Foul-free

www.frigoglass.com

## Retrofitting

ILOOK offers a unique and revolutionary retrofitting capability. Simply replacing the canopy, door and front grid of an FV unit, results in a new cooler with modern aesthetics and reliable performance.



## Technical data

	<b>FV 280</b> ILOOK	<b>FV 400</b> Ilook	FV 650 Ilook	<b>FV 1000</b> ILOOK	<b>FV 1200</b> Ilook
Dimensions					
External (WxDxH) mm	495 × 610 × 1612	595 × 610 × 1757	710 × 754 × 2030	1025 × 754 × 2030	1295 × 750 × 2030
Internal (WxDxH) mm	$\textbf{410} \times \textbf{529} \times \textbf{1216}$	511 × 529 × 1360	625 × 644 × 1581	941 × 572 × 1581	1211 × 644 × 1581
Net weight (kg)	92	105	147	185	240
Footprint area (m <sup>2</sup> )	0.35	0.45	0.61	0.84	1.09
Shelves					
Number of shelves (STD)	4	4	4	<b>4</b> + <b>4</b>	<b>4</b> + <b>4</b>
Facings per shelf	6	7	9	7 + 7	<b>8</b> + <b>8</b>
Total facings	42	56	90	140	160
Shelf size (WxD) mm	385 × 437	<b>480</b> × <b>437</b>	595 × 542	<b>460</b> × <b>547</b>	565 × 477
Capacity					
500ml PET	156	168	360	490	560
330ml cans	312	336	720	980	1120
Gross volume (lt)	265	368	627	936	1120
Energy					
R134a (kw/h per day)	2.32	2.66*	4.55	5.27	10.94
CO2 (kw/h per day)	2.81	3.07	4.40	5.51	8.06
Noise (dB)					
R134a	52	54	63	63	64
CO2	59	56	61	64	62
Transportation					
per 20' Container (units)	40	27	21	15	12
per 40' Container (units)	111	57	48	33	27
per 13.6 Truck (units)	90	63	51	36	30

\* Data for FV 400 is based on estimation



For your local sales representative please visit: **www.frigoglass.com**