FV 280



Key benefits

The ideal merchandising solution ideal for small turnover outlets for various trade channels

- · Slim, elegant design
- · Optimal height and footprint suits any kind of installations
- · Indoor and outdoor placement

Customer-friendly operation

· Self-closing door

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability & robustness in harsh environmental conditions
- High quality galvanized metal sheets for inner and outer cabin

Strong cooling performance

• Top performer in hot, dusty and humid environments

Easy servicing

 Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Reduced cost of ownership

· Foul-free condenser

Easy to rebrand and refurbish

Options

- IP24
- Bottle Opener & Crown catcher
- · Castor wheels
- Internal protector/stabilizer
- Voltage supervisor (cutter)
- Electric Leakage Circuit Breaker
- LED illumination
- Door lock

Technical data

Dimensions	
External (W/D/H) mm	495×610*×1612
Internal (W/D/H) mm	413×529×1217
Net weight (kg)	92
Footprint area (m²)	0.35
Shelves	
Number of shelves	3
Facings per shelf	6
Shelf size (W/D) mm	383 × 437

Capacity	
500 ml PET	156 max.**
330 ml cans	312 max.**
Gross volume (Lt)	269
Transportation	
per 20' container (units)	54
1 /	٥.
per 40' container (units)	114
per 40' container (units) per 13.6m truck (units)	٠.

