



Key benefits

The ideal merchandising solution for medium turnover outlets and various trade channels

- Indoor & outdoor placement
- Optimal footprint combined with large capacity

Customer-friendly operation

- Self-closing door

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability and robustness in harsh environmental conditions
- High quality galvanized metal sheets for inner and outer cabin

Strong cooling performance

- Top performer in hot, dusty and humid environments

Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Reduced cost of ownership

- Foul-free condenser

Options

- IP24
- Bottle Opener & Crown catcher
- Castor wheels
- Internal protector/stabilizer
- Voltage supervisor (cutter)
- Electric Leakage Circuit Breaker
- Door lock
- Thermometer (digital or analogue)
- Illuminated external canopy (top hat)
- LED illumination

Technical data

Dimensions	
External (W/D/H) mm	596 x 610* x 1758
Internal (W/D/H) mm	515 x 533 x 1361
Net weight (kg)	103
Footprint area (m ²)	0.45
Shelves	
Number of shelves	4
Facings per shelf	7
Shelf size (W/D) mm	476 x 437

Capacity	
500 ml PET	196 max.**
330 ml cans	441 max.**
Gross volume (Lt)	368
Transportation	
per 20' container (units)	27
per 40' container (units)	57
per 13.6m truck (units)	63



R134a