SP 400



Key benefits

Ideal merchandising solution for medium turnover outlets

- Outdoor and indoor placement
- · Optimal footprint to volume ratio
- · Self-closing door
- · Integrated handle with door for superior aesthetics

High reliability and robustness

- Galvanized metallic front grid, canopy, inner & outer cabin ensure durability & robustness in harsh environmental condition
- Widely proven ICM solution

Strong cooling performance

• Top performer in warm, dusty and humid environments

Strong brand visibility

- High quality and digitally printed stickers for side panels
- Illuminated internal canopy

Easy serviceability

 Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Options

Functional

- · Internal protector/stabilizer
- IP24
- · Rodent Mesh
- Hook lock
- · Castor wheels
- Bottle opener & crown catcher









Foul-free WOT

Best-in-class energy saving

IPS

Technical data

Dimensions	
External (W/D/H) mm	576 × 652 × 1766
Internal (W/D/H) mm	476 × 542 × 1311
Net weight (kg)	83
Footprint area (m²)	0.38
Shelves	

Shelves	
Number of shelves	4
Facings per shelf	7
Total facings	28
Shelf size (W/D) mm	460 × 491

Capacity	
500 ml PET	196
330 ml cans	392
Gross volume (Lt)	345
Transportation	
per 20' container (units)	TBD
per 40' container (units)	57

Energy	
Energy consumption (kWh/day)	
R134a	2.43
Noise (dB)	
R134a	58
	58