



# Super 60 sub Zero

## Key benefits

### The ideal merchandising solution for all trade channels

- Self-closing door
- Indoor and outdoor placement
- Energy efficient Subzero operation in Tropical ambient condition (41°C)

### High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability & robustness in harsh environmental condition
- High quality galvanized metal sheets for inner and outer cabin
- IP24

### Strong cooling performance

- Top performer in hot, dusty and humid environments

### Reduced cost of ownership

- Low-maintenance condenser
- LED illumination as standard

### Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

### Strong brand visibility

- Full size glass door for ultimate product visibility and enhanced impulse purchase
- High quality, digitally printed stickers for side panels



## Options

- External protector/ stabilizer (90/110V)
- Internal protector/stabilizer
- Glass tempering/ high altitude glass
- Castor wheels
- Bottle opener & crown catcher
- Digital temperature display



Foul-free  
WOT



Best-in-class  
energy saving



Reduced  
noise



IPS



Enhanced  
LED lighting

## Technical data

Dimensions	
External (W/D/H) mm	<b>739 x 685* x 2077</b>
Internal (W/D/H) mm	<b>655 x 540 x 1664</b>
Net weight (kg)	<b>119</b>
Footprint area (m <sup>2</sup> )	<b>0.58</b>
Shelves	
Number of shelves	<b>5</b>
Facings per shelf	<b>9</b>
Total facings (cans)	<b>108**</b>
Shelf size (W/D) mm	<b>623 x 485</b>

Capacity	
500 ml PET	<b>333**</b> max.
330 ml cans	<b>666**</b> max.
Gross volume (Lt)	<b>604</b>
Transportation	
per 20' container (units)	<b>24</b>
per 40' container (units)	<b>51</b>
per 13.6m truck (units)	<b>39</b>

\* Excluding back spacer \*\* with optional top shelf