

Super 60



Key benefits

The ideal merchandising solution for all trade channels

- Self-closing door
- Indoor and outdoor placement

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability & robustness in harsh environmental condition
- High quality galvanized metal sheets for inner and outer cabin
- IP24

Strong cooling performance

- Top performer in hot, dusty and humid environments

Reduced cost of ownership

- Low-maintenance condenser
- LED illumination as standard

Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Strong brand visibility

- Full size glass door for ultimate product visibility and enhanced impulse purchase
- High quality, silk-screen printed stickers for side panels



Options

- External protector/ stabilizer (90/110V)
- Internal protector/stabilizer
- Glass tempering/ high altitude glass
- Castor wheels
- Bottle opener & crown catcher



Foul-free
WOT



Best-in-class
energy saving



Reduced
noise



IPS



Enhanced
LED lighting

Technical data

Dimensions	
External (W/D/H) mm	739 x 685* x 2077
Internal (W/D/H) mm	655 x 540 x 1664
Net weight (kg)	119
Footprint area (m ²)	0.58
Shelves	
Number of shelves	5
Facings per shelf	9
Total facings (cans)	108**
Shelf size (W/D) mm	623 x 485

Capacity	
500 ml PET	333** max.
330 ml cans	666** max.
Gross volume (Lt)	604
Transportation	
per 20' container (units)	24
per 40' container (units)	51
per 13.6m truck (units)	39