ICOOL 1300

Key benefits

The ideal merchandising solution for outlets with high product turnover

- Coca-Cola exclusive ICM design to stand out at the POS
- Extended glass door for ultimate product visibility, ideal for many brands and SKUs
- · Increased illumination to enhance impulse buying
- · Indoor and outdoor placement (standard IP24)
- Self-closing doors
- Low noise operation

Increased reliability and robustness

- All ICOOL distinctive design components made of metal
- High quality galvanized metal sheets for cabin and grid
- User-friendly aluminum dye cast handle (applicable in the HC version)

Easy servicing

- Easy dis-/assembly and access to components e.g. front-sliding modules
- Use of quick electrical connectors

Reduced Cost of Ownership

- Low-maintenance condenser
- Standard LED illumination
- EC fan motors

Easy to rebrand and up-brand

Options

• Front visibility shelves

Various lock types

- Door blocker
- Protection against current leakage to earth
- Heater

provision

- Night cover
- Internal protector/stabilizer
- Available in Hinged (HD) and Sliding (SD) versions



(HD version)



Technical data

Left-right door opening

Dimensions	
External (W/D/H) mm (HD/SD)	1310 × 763* × 2139/2125
Internal (W/D/H) mm	$\textbf{1210} \times \textbf{623} \times \textbf{1700}$
Net weight (kg) (HD/SD)	210 / 220
Footprint area (m ²)	1.00
Shelves	
Number of shelves	10
Facings per shelf	16

Shelves continued	
Total facings	192
Shelf size (W/D) mm (HD/SD)	595 × 525 / 595 × 466
Capacity**	
500 ml PET (HD/SD)	640 cert. / 624 cert.
330 ml cans (HD/SD)	1728 max. / 1512 max.
Gross volume (Lt) (HD/S	D) 1340 / 1189

Transportation		
per 40' container (units)	22	
per 13.6m truck (units)	30	
Energy		
Energy consumption (kWh/day)		
(HD/SD)	4.3 / 4.1	
Noise		
Noise (dB)	59	

*Excluding 80mm back spacer in HD and SD versions and 40mm handle in HD version ** All SKUs aligned