

Super 1100



Key benefits

The ideal double-door ICM solution for various trade channels

- Moderate footprint and large capacity
- Indoor and outdoor placement
- Self-closing door

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability and robustness in harsh environmental conditions
- High quality galvanized metal sheets for inner and outer cabin
- IP24

Strong cooling performance

- Top performer in hot, dusty and humid environments

Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Reduced cost of ownership

- Low-maintenance condenser
- LED illumination as standard

Strong brand visibility

- Full size glass door for ultimate product visibility and enhanced impulse purchase
- High quality, silk-screen printed stickers for side panels



Options

- External protector/ stabilizer (90/110V)
- Internal protector/stabilizer
- Glass tempering/ high altitude glass
- Castor wheels
- Bottle opener & crown catcher

Technical data

Dimensions	
External (W/D/H) mm	1027 x 745* x 2077
Internal (W/D/H) mm	941 x 648 x 1581
Net weight (kg)	171
Footprint area (m ²)	0.91
Shelves	
Number of shelves	5 + 5
Facings per shelf	7 + 7
Shelf size (W/D) mm	450 x 475

Capacity	
500 ml PET	490 max.
330 ml cans	980 max.
Gross volume (Lt)	960
Transportation	
per 20' container (units)	15
per 40' container (units)	33
per 13.6m truck (units)	36

* Excluding handle & back spacer