

Super 45 sub Zero



Key benefits

The ideal merchandising solution for all trade channels

- Self-closing door
- Indoor and outdoor placement
- Energy efficient Subzero operation in Tropical ambient condition (41°C)

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability & robustness in harsh environmental condition
- High quality galvanized metal sheets for inner and outer cabin
- IP24

Strong cooling performance

- Top performer in hot, dusty and humid environments

Reduced cost of ownership

- Low-maintenance condenser
- LED illumination as standard

Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Strong brand visibility

- Full size glass door for ultimate product visibility and enhanced impulse purchase
- High quality, digitally printed stickers for side panels



Options

- External protector/ stabilizer (90/110V)
- Internal protector/stabilizer
- Glass tempering/ high altitude glass
- Castor wheels
- Bottle opener & crown catcher
- Digital temperature display



Foul-free WOT



Best-in-class energy saving



Reduced noise



IPS



Enhanced LED lighting

Technical data

Dimensions	
External (W/D/H) mm	576 x 630* x 2069
Internal (W/D/H) mm	492 x 540 x 1664
Net weight (kg)	104
Footprint area (m²)	0.37
Shelves	
Number of shelves	5
Facings per shelf	7
Total facings (cans)	84**
Shelfsize(W/D)mm***	460 x 444

Capacity	
500 ml PET	273** max.
330 ml cans	532** max.
Gross volume (Lt)	449
Transportation	
per 20' container (units)	27
per 40' container (units)	57
per 13.6m truck (units)	50

* Excluding back spacer **with extended shelves and optimal top shelf ***uncoated shelf dims