FV 650 FFD

Key benefits

The ideal merchandising solution for various trade channels

Indoor & outdoor placement

Customer-friendly operation

Self-closing door

High reliability and robustness

- Widely-proven ICM solution
- · Aluminum door frame and metallic front grid ensure durability and robustness in harsh environmental conditions
- · High quality galvanized metal sheets for inner and outer cabin

Strong cooling performance

• Top performer in hot, dusty and humid environments

Easy servicing

· Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Reduced cost of ownership

- Foul-free condenser
- LED illumination

Easy to rebrand and refurbish



Options

- Visi-shelves
- High-density shelves
- IP24

- Thermometer (digital
 - or analogue)

- Voltage supervisor (cutter)
- Door lock
- Night Cover Internal protector/stabilizer
 Bottle opener & Crown catcher
 - Electromagnetic lock

Technical data

| Dimensions | |
|----------------------------------|--|
| External (W/D/H) mm | $\textbf{710} \times \textbf{730*} \times \textbf{2045}$ |
| Internal (W/D/H) mm | 625 × 644 × 1580 |
| Net weight (kg) | 133 |
| Footprint area (m ²) | 0.51 |
| Shelves | |
| Number of shelves | 5 |
| Facings per shelf | 9 |
| Shelfsize(W/D)mm*** | 595 × 545 |

| Capacity | |
|--|-------------------|
| 500 ml PET | 385 max.** |
| 330 ml cans | 770 max.** |
| Gross volume (Lt) | 636 |
| | |
| Transportation | |
| Transportation per 20' container (units) | 21 |
| • | 21 48 |