

Easy Reach Express 2.0

Key benefits

- Modern and dynamic design
- Very low energy consumption
- Maximum product visibility with 3 loading levels

Technology and Performance

- Reliable and robust construction
- WOT condenser
- Best in class energy performance 3,36 kWh/24h
- Easy serviceability with quick electrical connectors and easy access components
- Natural refrigerant R290
- Silent operation
- Optimized airflow circulation

Standard configuration

- Side panels branded with silk screen stickers
- Front area branded with silk screen printing
- 2 front vertical cool white LED lighting
- Electronic controller
- Grey inner cabinet color
- Front left and right transparent flaps
- 2 shelves
- 4 rollers / 2 adjustable feet



Options

- PRCD protection
- RCCB protection
- Castor wheels
- Double tempered glass
- Hidden RGB LED light
- Price profiles

Technical data

Dimensions		Shelves		Capacity	
External (W/D/H) mm	655 x 732 x 1410	Loading levels	3	500 ml PET	120
Internal (W/D/H) mm	565 x 565 x 1025	Facings per shelf	8	330 ml cans	240
Net weight (kg)	97	Total facings	24	Gross volume (Lt)	214
Gross weight (kg)	113	Shelf size (W/D) mm	535 x 272 (upper)	Transportation	
Footprint area (m ²)	0.48		535 x 337 (middle)	per 20' container (units)	22
			543 x 404 (bottom)	per 40' container (units)	45
				per 13.6m truck (units)	54