



Key benefits

- Modern and elegant design without canopy
- Maximum product visibility with 7 loading levels
- Optimized merchandizing effectiveness

Technology and Performance

- Reliable and robust construction
- No maintenance condenser
- Energy Class C
- Easy serviceability with quick electrical connectors and easy access components
- Natural refrigerant R290
- Silent operation dBA <57
- Optimized airflow circulation with dual evaporator and condenser motors

Standard Configuration

- Top sticker on door
- Side stickers
- Vertical side LED
- Easy grip handle
- Electronic thermostat
- Metallic outer cabin, inner cabin and door
- 6 adjustable shelves
- Self-closing door
- 4 rollers / 2 adjustable feet



Options

- Light switch
- Compressor switch
- PRCD/RCCB protection
- Additional LED lighting
- Left/right door opening
- High density shelves
- Pad lock provision
- Door blocker
- Price profiles
- Electromagnetic lock & eye lock



Best-in-class energy saving



Low noise

Technical data

Dimensions		Shelves		Capacity	
External (W/D/H) mm	595 x 676* x 2012	Loading levels	7	500ml PET	259 cert.
Internal (W/D/H) mm	521 x 491 x 1818	Facings per shelf	7	330ml cans	518 max.
Net weight (kg)	100	Total facings	49	Gross volume (lt)	472
Footprint area (m ²)	0,38	Shelf size (W/D) mm	508 x 423	Transportation	
				per 40' container (units)	57
				per 13.6m truck (units)	76 (wide truck)
					66 (standard truck)

*Including handle (32mm)